



CLOSE COUPLED PUMP

For specific requirements of centrifugal pumps where the pump impeller is mounted directly on the motor shaft.

HP – 1 through 60 HP

Phase – Single and Three Phase

RPM – 1800 and 3600

Voltage

- 115/230
- 230
- 575
- 208-230/460
- 200
- 230/460

Efficiency – Standard, Energy and Premium Efficient

Enclosure

- Open Dripproof (ODP)
- Totally Enclosed Fan Cooled (TEFC)
- Hazardous Location

Mounting – Footed and Footless

Shaft Types

- JM
- JP
- Westcoast



Close Coupled Pump ODP Motor



Close Coupled Pump TEFC Motor

U.S. Motors® brand Close Coupled Pump Motors are designed to meet a variety of applications

SINGLE PHASE

- Open Dripproof (ODP)
 - JM Shaft Footed
 - JP Shaft Footed
- Totally Enclosed Fan Cooled (TEFC)
 - JM Shaft Footed
 - JP Shaft Footed

THREE PHASE

- Open Dripproof Standard and Premium Efficient
 - JM Shaft Footed & Footless
 - JP Shaft Footed & Footless
 - Westcoast Shaft Footed (Standard Efficient only)
- Open Dripproof Energy Efficient
 - JM Shaft Footed
 - JP Shaft Footed
- Hazardous Location, Dual Label
 - JM Shaft Footed
- Totally Enclosed Fan Cooled (TEFC) Standard and Energy Efficient
 - JM Shaft Footed
 - JP Shaft Footed
 - Westcoast Footed (Standard Efficient Only)
- Totally Enclosed Fan Cooled (TEFC) Premium Efficient
 - JM Shaft Footed